

GAS ENGINE HEAT PUMP

TECHNICAL DATA WITH HYDROBOX

ENCP...L1			450	560	710	850	
Rated heating capacity (with Hydrobox) ¹⁾	A7 / W35	kW	51	64	79	89	
Heating capacity (with Hydrobox) ¹⁾	A-10 / W35	kW	51	57	71	77	
Rated cooling capacity (with Hydrobox) ¹⁾	A35 / W7	kW	43	53	64	70	
Cooling capacity (with Hydrobox) ¹⁾	A35 / W15	kW	52	64	77	85	
Dimensions ²⁾	H x W x D	mm	2.288 x 1.690 x 830				
Weight	(without/with heat recovery)	kg	785 / 795	805 / 815	885 / 895	890 / 900	
Electrical characteristics	Power supply	V/Ph/Hz	230 / 1 / 50				
	Starting current	A	20				
	Operating current heating / cooling	A	3,68 / 7,71	3,29 / 6,80	7,26 / 8,14	8,22 / 10,45	
	Power consumption heating / cooling	kW	0,73 / 1,41	0,58 / 1,24	1,33 / 1,51	1,51 / 1,96	
Fuel data	Gas type		Natural gas I3E (optional LPG I3P)				
	Rated gas consumption (LHV) heating / cooling	kW	30 / 33	38 / 40	51 / 54	60 / 63	
	Max. gas consumption (LHV)	kW	58	63	80	87	
	Gas supply pressure	mbar	17–25				
Engine	Type		YANMAR four-stroke engine, water-cooled				
	Cylinder		3		4		
	Cubic capacity	cm ³	1,642		2,190		
	Speed range	Heating	1 / min	650–2,550	650–2,800	650–2,600	650–2,800
		Cooling	1 / min	650–1,600	650–1,900	650–2,100	650–2,350
	Lubricant oil	Type		YANMAR genuine GEHP oil			
Quantity		l	36	40	46	51	
Cooling water engine	Type		YANMAR genuine LLC				
	Quantity	l	23		29		
	Concentration	%	50				
Compressors	Type		Scroll				
	Quantity		2		3		
	Power transmission		Poly-V flat belt				
Refrigerant	Type		R410A				
	Quantity	kg	9				
Fans	Type		Axial				
	Quantity		2				
	Related air flow	m ³ /h	28,200	30,600	31,800	33,600	
	External pressure (max.)	Pa	5 (30)				
Sound pressure level ³⁾ (sound power level)	Nominal	dB(A)	62,7 (83)	62,0 (83)	65,0 (85)	68,2 (87)	
	Quiet mode	dB(A)	53,6 (80)	55,4 (80)	57,1 (82)	61,0 (84)	
	Maximum (heating mode)	dB(A)	67 (87)	68 (88)	67 (87)	69 (89)	
Pipe connections	Refrigeration gas / liquid pipe ⁴⁾	Inch	1 ½ / ½	1 ½ / ¾	1 ¼ / ¾	1 ¼ / ¾	
	Exhaust pipe (outside diameter)	mm	89				
	Fuel gas pipe	Inch	R 3 / 4				
	Drain pipe (inside diameter)	mm	16				
	Exhaust drain pipe (inside diameter)	mm	15				
Maintenance interval engine / engine oil ⁵⁾		h	10,000 / 20,000				
Heating capacity heat recovery	Cooling mode, 100 % load	kW	16,0	20,5	28,5	30,0	
	Heating mode, 35 % load	kW	5,0	6,0	10,0	11,0	

1) Capacities, electrical characteristics and fuel consumptions are calculated for a standard indoor/outdoor unit combination with a 7.5 m piping length and 0 m level difference.

These are Hydrobox water outlet temperatures.

2) See accessories for dimensions with vibration dampers.

3) The operating noise levels shown above were measured at a distance of 1 m to the front face of each unit and at a height of 1.5 m and then converted into an anechoic room equivalent level. The noise level of the actually installed unit is usually higher than the indicated value due to influences of ambient noise and echo.

4) The dimensions of the refrigerant connection pipes can be found in the installation manual.

5) Depending on working and operating conditions.